



# International Polishing Technology Limited

4 – Access 18  
BRISTOL BS11 8HT Great Britain  
Telephone: +44 (0)33 3240 0067  
Fax: +44 (0) 033 3240 0068  
Email: office@liquidshine.eu

## MATERIAL SAFETY DATA SHEET

**CRITERIA: NON HAZARDOUS**

Date of issue: 20-6-2008

### IDENTIFICATION

**PRODUCT NAME:** Cutting Compound - High Cut

**U.N. NUMBER:** None

**HAZCHEM CODE:** None

**POISONS SCHEDULE:** None

**USE:** Liquid abrasive composition for polishing paint and plastics.

#### **PHYSICAL DESCRIPTION/PROPERTIES:**

Paste, consisting of aluminium oxide particles suspended in an aqueous emulsion of hydrocarbon, mineral oil, and polysorbate surfactant.

#### **INGREDIENTS:**

Aliphatic hydrocarbons CAS 64742-47-8	<50%
Aluminium oxide CAS 1344-28-1	<50%
Kaolin CAS 66402-68-4	<10%
Sorbitan oleate CAS 26266-58-0	<5%
Rem. Water.	

### HEALTH HAZARD INFORMATION

#### **HEALTH EFFECTS**

**SWALLOWED:** May cause diarrhoea

**EYE:** Strongly irritating

**SKIN:** Prolonged exposure may cause dermatitis

**INHALED:** Inhaled spray will cause sneezing

#### **FIRST AID:**

**SWALLOWED:** Give water to drink. Do not induce vomiting Call for medical attention.

**EYE:** Wash with plenty of water

**SKIN:** Wash with water

**INHALED:** Keep at rest. Call for medical attention.

## PRECAUTIONS FOR USE

**EXPOSURE LIMITS:** The maximum exposure limit for hydrocarbon is 300 PPM.

**VENTILATION:** Ventilation is required as for all polishing operations.

**PERSONAL PROTECTION:** Wear safety glasses, long sleeves and chemical resistant gloves. Where concentration in air exceed 300 PPM, approved respirators (AS/NZS1715 and AS/NZS1716 may be necessary to prevent overexposure by inhalation.

**FLAMMABILITY:** Low hazard. Material can form flammable mixtures or can burn only upon heating to temperatures at or above the flash point, which is > 130 DegC (PMCC)

## SAFE HANDLING INFORMATION

**STORAGE AND TRANSPORT:** No storage or transport restrictions.

**SPILLS AND DISPOSAL:** Spills are slippery. Shovel spills into garbage bin and hose residue away with water.

**FIRE / EXPLOSION HAZARD:** Low hazard. Material can form flammable mixtures or can burn only upon heating to temperatures at or above the flash point, which is > 130 DegC (PMCC)  
Before the flash point temperature can be reached all water in the product has to boil off.